

# NLS-HR2180

## 2D Handheld Barcode Scanner



### Features

#### ■ Outstanding Performance

Equipped with an outstanding CPU, this CPU-based scanner can effortlessly capture high-density, high-volume and distorted barcodes printed on paper or displayed on screen.

#### ■ Elegant Appearance

Blending ergonomics and aesthetics in its design, the NLS-HR2180 not only ensures operator comfort and productivity for intensive handheld scanning but also meets the aesthetic

#### ■ Cost-effective Solution

The NLS-HR2180 provides a cost-effective data capture solution that allows customers to enjoy the capabilities of 2D barcode scanner for the price of 1D scanner.

#### ■ Durable Construction

The NLS-HR2180, built into an IP42-sealed and drop resistant (1.2m) housing with no moving parts, fortifies itself inside and out.

### Application Scenarios

O2O applications, purchase-sales-inventory management, ticket/voucher management, office automation.

## 2D Handheld Barcode Scanner

<b>Performance</b>	Image Sensor	640×480 CMOS	
	Illumination	White LED	
	Aiming	Red LED (625nm)	
	Symbologies	2D	PDF417, Micro PDF417, Micro QR, QR Code, Data Matrix, Aztec
		1D	Code 11, Code 128, Code 39, GS1-128 (UCC/EAN 128), AIM 128, ISBT 128, Codabar, Code 93, UPC-A, UPC-E, Coupon, GS1 Composite, EAN-8, EAN-13, ISBN/ISSN, Interleaved 2 of 5, Matrix 2 of 5, Industrial 25, ITF6, ITF-14, Standard 25, China Post 25, MSI Plessey, Plessey, GS1 Databar (RSS)
	Resolution*	≥3mil (Code 128)	
	Typical Depth of Field*	EAN-13	50mm-260mm (13mil)
		Code 39	50mm-115mm (5mil)
		PDF 417	50mm-120mm (6.7mil)
		Data Matrix	35mm-125mm (10mil)
		QR Code	30mm-170mm (15mil)
	Scan Angle**	Pitch	±55° (QR 15mil)
		Roll	360° (QR 15mil)
Skew		±55°(QR 15mil)	
Field of View	Horizontal 45°, Vertical 34°		
Min. Symbol Contrast	20%		
<b>Physical</b>	Interfaces	RS-232, USB	
	Dimensions (L×W×H)	145×101×68mm	
	Weight	111g	
	Notification	Beep, LED indicator	
	Operating Voltage	5VDC±5%	
	Rated Power Consumption	950mW (typical)	
	Current @ 5VDC	Operating	190mA (typical), 201mA (max.)
		Idle	35mA
	<b>Environmental</b>	Operating Temperature	-20°C to 60°C (-4°F to 140°F)
Storage Temperature		-40°C to 70°C (-40°F to 158°F)	
Humidity		5% ~ 95% (non-condensing)	
ESD		±15 KV (air discharge); ±8 KV (direct discharge)	
Drop		1.2m	
Sealing		IP42	
<b>Certifications</b>	FCC Part15 Class B, CE EMC Class B		

\*Specifications are subject to change without notice.\*

Version: V1.1

**Newland China**  
+86-591-83978605  
contact@nlsan.com  
www.newlandaidc.com

**Newland Europe**  
+31(0)-345-87-0033  
info@newland-id.com  
www.newland-id.com

**Newland North America**  
+1-510-490-3888  
info@newlandna.com  
www.newlandamerica.com

**Newland Latin America**  
+1-239-598-0068  
info@newlandla.com  
www.newlandamerica.com

**Newland Taiwan**  
+886-2-7731-5388  
info@newland-id.com.tw  
www.newland-id.com.tw

**Newland Korea**  
+82-10-8990-4838  
th.sung@newland-id.com  
www.newlandaidc.com